CLEANER T-VR

SAFETY DATA SHEET

Compiled in accordance with REACH Regulation (EC) No 1907/2006, as retained and amended in UK law

ISSUE DATE: 10.08.2018
REVISION DATE: 08.04.2026
SUPERSEDES: 21.08.2025
VERSION: 4.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	:	Mixture
Trade name	:	Cleaner T-VR
Product code	:	Ford Internal Ref.: 200321
SDS Number	:	4292
Unique Formula Identifier (UFI)	:	V7VM-GQY3-RU1G-M9HS
Product use	:	Professional use

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Function or use category	:	Cleaner

1.2.2. Uses advised against

Restrictions on use	:	None known

1.3. Details of the supplier of the safety data sheet

Supplier
Ford-Werke GmbH
Edsel-Ford-Str. 2-14
50769 Cologne
Germany
+49 221 90-33333
sdseu@ford.com

Distributor
Ford Motor Company Ltd.
Parts Distribution Centre
Royal Oak Way South
NN11 8NT Daventry, Northants
United Kingdom
+44 1327 305 198

1.4. Emergency telephone number

+49 (0) 6132-84463 (GBK GmbH – 24/7)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations

Physical hazards	Flammable liquids, Category 2	H225	Highly flammable liquid and vapour.
Health hazards	Skin corrosion/irritation, Category 2	H315	Causes skin irritation.
	Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336	May cause drowsiness or dizziness.
	Specific target organ toxicity – Repeated exposure, Category 2	H373	May cause damage to organs through prolonged or repeated exposure.
	Aspiration hazard, Category 1	H304	May be fatal if swallowed and enters airways.
Environmental hazards	Hazardous to the aquatic environment – Chronic Hazard, Category 2	H411	Toxic to aquatic life with long lasting effects.

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations

Hazard pictograms



Signal word Danger

Contains Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane; n-hexane

Hazard statements

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing vapours.

P273 Avoid release to the environment.

Response

P301+P310+P331 IF SWALLOWED: Immediately call a POISON CENTER, a doctor. Do NOT induce vomiting.

P370+P378 In case of fire: Use carbon dioxide (CO2), extinguishing powder, alcohol resistant foam to extinguish.

P391 Collect spillage.

Storage

P403+P235 Store in a well-ventilated place. Keep cool.

2.3. Other hazards

Other hazards which do not result in classification : Solvents contained in the product evaporate during processing. Vapours may form flammable and explosive mixture with air. Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII.
This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII.

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical name	CAS- No EC- No Index No RRN	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Notes
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	921-024-6 01-2119475514-35-XXXX	80 -< 100	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411	UVCB
n-hexane	110-54-3 203-777-6 601-037-00-0	1 -< 3	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361f	# substance listed as REACH Candidate

	01-2119480412-44-XXXX		STOT SE 3, H336 STOT RE 1, H372 Asp. Tox. 1, H304 Aquatic Chronic 2, H411	

Comments : #: substance with a Community workplace exposure limit
UVCB: Substances of Unknown or Variable composition, Complex reaction products or Biological materials

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Call a physician if symptoms develop or persist.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a physician if symptoms develop or persist.

First-aid measures after skin contact : Gently wash with plenty of soap and water. Take off immediately all contaminated clothing. Get medical attention if symptoms occur.

First-aid measures after eye contact : Remove contact lenses, if present and easy to do. Continue rinsing. Immediately flush eyes thoroughly with water for at least 15 minutes. Get medical attention if symptoms occur.

First-aid measures after ingestion : Rinse mouth out with water. Drink 1 or 2 glasses of water. Do NOT induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects: : May cause drowsiness or dizziness. Aspiration may cause pulmonary oedema and pneumonitis. Skin irritation.

Symptoms/effects after inhalation : May cause drowsiness or dizziness.

Symptoms/effects after skin contact : Causes skin irritation.

Symptoms/effects after eye contact : May cause eye irritation.

Symptoms/effects after ingestion : May be fatal if swallowed and enters airways. Risk of lung oedema.

4.3. Indication of any immediate medical attention and special treatment needed

Do not induce vomiting. Symptoms may be delayed.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media : Do not use a water jet since it may cause the fire to spread.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Highly flammable liquid and vapour.

Hazardous decomposition products in case of fire : Toxic fumes may be released. Carbon oxides (CO, CO2).

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment : For personal protection, see section 8 of the SDS.

Emergency procedures : Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources if safe to do so. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Ventilate spillage area. Local authorities should be advised if significant spillages cannot be contained.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

Emergency procedures	:	Keep unnecessary personnel away.

6.2. Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up

For containment	:	Collect spillage.
Methods for cleaning up	:	Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Contain or absorb spilled liquid with non-combustible material. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Small spills: Wipe up with absorbent material (for example cloth). Clean surface thoroughly to remove residual contamination. Never return spills in original containers for re-use.
Other information	:	Eliminate ignition sources. Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil etc) away from spilled material. If possible try to contain floating material. Cover material with sodium carbonate (Na2CO3) or 1:1 mixture of soda ash and slaked lime. Collect and dispose of spillage as indicated in section 13. Clean surface thoroughly to remove residual contamination. Product decomposed by water must be neutralized.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For disposal of residues refer to section 13 :" Disposal considerations".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	:	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Use only outdoors or in a well-ventilated area.
Hygiene measures	:	Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	:	Ground/bond container and receiving equipment.
Storage conditions	:	Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.
Storage temperature	:	5 – 25 °C

7.3. Specific end use(s)

Cleaner.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. National occupational exposure and biological limit values

n-hexane (110-54-3)

EU - Indicative Occupational Exposure Limit (IOEL)

Local name	n-Hexane
IOEL TWA	72 mg/m³
	20 ppm
Regulatory reference	COMMISSION DIRECTIVE 2006/15/EC

United Kingdom - Occupational Exposure Limits

Local name	n-Hexane
WEL TWA (OEL TWA)	72 mg/m³
	20 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	773 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	2035 mg/m³
DNEL/DMEL (General population)	
Long-term - systemic effects,oral	699 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	608 mg/m³
Long-term - systemic effects, dermal	699 mg/kg bodyweight/day

n-hexane (110-54-3)

DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	11 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	75 mg/m³
DNEL/DMEL (General population)	
Long-term - systemic effects,oral	4 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	16 mg/m³
Long-term - systemic effects, dermal	5.3 mg/kg bodyweight/day

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:
Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

8.2.2. Personal protection equipment

8.2.2.1. Eye and face protection

Eye protection:
Wear security glasses which protect from splashes. EN 166.

8.2.2.2. Skin protection

Skin and body protection:
Wear suitable protective clothing. Long sleeved protective clothing

Hand protection:
protective gloves. DIN ISO 374. The recommendation is only valid for the supplied product and the stated application. Special working conditions, like heat or mechanical strain, which deviate from the test conditions, can reduce the protective effect provided by the recommended glove

Material	Permeation	Thickness (mm)	Comments
Nitrile rubber (NBR)	6 (> 480 minutes)	0,4	Glove recommendation: Camatril Velours® 730 (Kächele-Cama GmbH, source of supply see www.kcl.de) or comparable product.
In case of splash contact: Nitrile rubber (NBR)	6 (> 480 minutes)	0,4	Glove recommendation: Camatril Velours® 730 (Kächele-Cama GmbH, source of supply see www.kcl.de) or comparable product.

Other skin protection

Materials for protective clothing:

Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Respiratory protection

Device	Filter type	Condition	Standard
Breathing apparatus with filter	ABEK-P2		

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	:	Liquid
Colour	:	Colourless.
Odour	:	Hydrocarbon-like.
Odour threshold	:	Not available
Melting point	:	Not applicable
Freezing point	:	> -30 °C
Boiling point	:	89 – 107 °C
Flammability	:	Not applicable
Explosive limits	:	Not available
Lower explosive limit (LEL)	:	1 Vol-%
Upper explosive limit (UEL)	:	8 Vol-%
Flash point	:	-15.5 °C (closed cup)
Auto-ignition temperature	:	268 °C
Decomposition temperature	:	> 200 °C
pH	:	Not available
Viscosity, kinematic	:	0.61 mm²/s @ 20°C
Solubility	:	insoluble in water.
Log Kow	:	Not available
Vapour pressure	:	85 hPa @ 20°C
Vapour pressure at 50°C	:	290 hPa
Density	:	0.705 g/cm³ @ 20°C
Relative density	:	Not available
Relative vapour density at 20°C	:	0.72 @ 15°C
Particle size	:	Not applicable
Particle size distribution	:	Not applicable
Particle shape	:	Not applicable
Particle aspect ratio	:	Not applicable
Particle aggregation state	:	Not applicable
Particle agglomeration state	:	Not applicable
Particle specific surface area	:	Not applicable
Particle dustiness	:	Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

VOC content	:	100 %

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts with (strong) oxidizers.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

Strong oxidizers.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Based on available data, the classification criteria are not met
Acute toxicity (dermal) : Based on available data, the classification criteria are not met
Acute toxicity (inhalation) : Based on available data, the classification criteria are not met
Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Based on available data, the classification criteria are not met
Respiratory or skin sensitisation : Based on available data, the classification criteria are not met
Germ cell mutagenicity : Based on available data, the classification criteria are not met
Carcinogenicity : Based on available data, the classification criteria are not met
Reproductive toxicity : Based on available data, the classification criteria are not met
STOT-single exposure : May cause drowsiness or dizziness.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	
STOT-single exposure	May cause drowsiness or dizziness.

n-hexane (110-54-3)	
STOT-single exposure	May cause drowsiness or dizziness.

STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.

n-hexane (110-54-3)	
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard : May be fatal if swallowed and enters airways.

Cleaner T-VR	
Viscosity, kinematic	0.61 mm²/s @ 20°C

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Adverse health effects caused by endocrine disrupting properties : The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

11.2.2. Other information

Potential adverse human health effects and symptoms : Likely routes of exposure,Inhalation,May cause drowsiness or dizziness,Skin contact :Causes skin irritation,Eye contact,Direct contact with eyes may cause temporary irritation,Ingestion,Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	:	Toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short–term (acute)	:	Based on available data, the classification criteria are not met
Hazardous to the aquatic environment, long–term (chronic)	:	Toxic to aquatic life with long lasting effects.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

LC50 - Fish [1]	11.4 mg/l LL50; 96h; Oncorhynchus mykiss (Rainbow trout); (OECD 203 method)
EC50 - Crustacea [1]	3 mg/l EL50; 48h; Daphnia magna (Water flea); (OECD 202 method)
NOEC chronic crustacea	0.17 mg/l 21 d; Daphnia magna (Water flea); (OECD 211 method)

n-hexane (110-54-3)

LC50 - Fish [1]	> 1 – 10 mg/l 96 h; (OECD 203 method)
EC50 - Crustacea [1]	2.1 mg/l 48h; Daphnia magna (Water flea)(OECD 202 method)
EC50 72h - Algae [1]	> 1 – 10 mg/l 72 h; (OECD 201 method)

12.2. Persistence and degradability

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Persistence and degradability	Readily biodegradable.
Biodegradation	98 % (OECD 301F method)

n-hexane (110-54-3)

Persistence and degradability	Readily biodegradable.
Biodegradation	81 % (OECD 301F method)

12.3. Bioaccumulative potential

n-hexane (110-54-3)

Log Pow	4

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

Cleaner T-VR

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII.

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII.

12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties	:	The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

12.7. Other adverse effects

Other adverse effects	:	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this product

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional waste regulation	:	Disposal must be done according to official regulations.
Waste treatment methods	:	Dispose of contents/container in accordance with licensed collector's sorting instructions.

Additional information	:	Flammable vapours may accumulate in the container.
Ecological waste information	:	Avoid discharge into drains, water courses or onto the ground.
European List of Waste (LoW, EC 2000/532)	:	14 06 03* - other solvents and solvent mixtures 15 01 10* - packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

14.1. UN number or ID number

UN-No. (ADR)	:	UN 1268
UN-No. (IMDG)	:	UN 1268
UN-No. (IATA)	:	UN 1268
UN-No. (ADN)	:	UN 1268
UN-No. (RID)	:	UN 1268

14.2. UN proper shipping name

Proper Shipping Name (ADR)	:	PETROLEUM DISTILLATES, N.O.S.
Proper Shipping Name (IMDG)	:	PETROLEUM DISTILLATES, N.O.S.
Proper Shipping Name (IATA)	:	Petroleum distillates, n.o.s.
Proper Shipping Name (ADN)	:	PETROLEUM DISTILLATES, N.O.S.
Proper Shipping Name (RID)	:	PETROLEUM DISTILLATES, N.O.S.

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR)	:	3
Danger labels (ADR)	:	3

IMDG

Transport hazard class(es) (IMDG)	:	3
Danger labels (IMDG)	:	3

IATA

Transport hazard class(es) (IATA)	:	3
Hazard labels (IATA)	:	3

ADN

Transport hazard class(es) (ADN)	:	3
Danger labels (ADN)	:	3

RID

Transport hazard class(es) (RID)	:	3
Danger labels (RID)	:	3

14.4. Packing group

Packing group (ADR)	:	II
Packing group (IMDG)	:	II
Packing group (IATA)	:	II
Packing group (ADN)	:	II
Packing group (RID)	:	II

14.5. Environmental hazards

Dangerous for the environment	:	Yes
Marine pollutant	:	Yes
Other information	:	No supplementary information available.

14.6. Special precautions for user

Overland transport

Classification code (ADR)	:	F1
Special provisions (ADR)	:	640D, 664
Limited quantities (ADR)	:	1l

Packing instructions (ADR)	:	P001, IBC02, R001
Hazard identification number (Kemler No.)	:	33
Tunnel restriction code (ADR)	:	D/E
EAC code	:	3YE

Transport by sea

Limited quantities (IMDG)	:	1 L
Packing instructions (IMDG)	:	P001
EmS-No. (Fire)	:	F-E
EmS-No. (Spillage)	:	S-E
Stowage category (IMDG)	:	B

Air transport

PCA Excepted quantities (IATA)	:	E2
PCA Limited quantities (IATA)	:	Y341
PCA limited quantity max net quantity (IATA)	:	1L
PCA packing instructions (IATA)	:	353
PCA max net quantity (IATA)	:	5L
CAO packing instructions (IATA)	:	364
CAO max net quantity (IATA)	:	60L
Special provisions (IATA)	:	A3
ERG code (IATA)	:	3H

Inland waterway transport

Classification code (ADN)	:	F1
Special provisions (ADN)	:	640D
Limited quantities (ADN)	:	1 L
Carriage permitted (ADN)	:	T

Rail transport

Classification code (RID)	:	F1
Special provisions (RID)	:	640D
Limited quantities (RID)	:	1L
Packing instructions (RID)	:	P001, IBC02, R001
Hazard identification number (RID)	:	33

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

EU restriction list (REACH Annex XVII)

Reference code	Applicable on
3(a)	Cleaner T-VR ; Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane ; n-hexane
3(b)	Cleaner T-VR ; Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane ; n-hexane
3(c)	Cleaner T-VR ; Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane ; n-hexane

Contains substance(s) listed on the REACH Candidate List in concentrations ≥ 0.1 % or SCL: n-hexane (EC 203-777-6, CAS 110-54-3)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

VOC content	:	100 %
Other information, restriction and prohibition regulations	:	Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work, as amended. Directive 94/33/EC on the protection of young people at work, as amended. Directive 92/85/EEC on the safety and health of pregnant workers and workers who have recently given birth or are breastfeeding as amended. For details, refer to section 3 and 8.

Directive 2012/18/EU (SEVESO III)

Seveso Additional information	:	Not applicable

Seveso III Part I (Categories of dangerous substances)	Qualifying quantity (tonnes)	
	Lower-tier	Upper-tier
E2 Hazardous to the Aquatic Environment in Category Chronic 2	200	500

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes:

UFI. Label elements. Supplemental hazard information. Information on ingredients. Physical and chemical properties. Transport information. Regulatory information.

Abbreviations and acronyms

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DNEL	Derived-No Effect Level
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PCA	Passenger and Cargo Aircraft
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
RRN	REACH Registration no.
SDS	Safety Data Sheet
STEL	Short-term Exposure Limit
STP	Sewage treatment plant
TLM	Median Tolerance Limit
TWA	Time Weighted Average. The average concentration of a chemical in air over the total exposure time-usually an 8-hour workday.
VOC	Volatile organic compounds
vPvB	Very Persistent and Very Bioaccumulative

Data sources	:	REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.
Training advice	:	Normal use of this product shall imply use in accordance with the instructions on the packaging.

Full text of H- and EUH-statements

Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Repr. 2	Reproductive toxicity, Category 2

Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 1	Specific target organ toxicity – Repeated exposure, Category 1
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H361f	Suspected of damaging fertility.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]

Flam. Liq. 2	H225	On the basis of test data
Skin Irrit. 2	H315	Calculation method
STOT SE 3	H336	Calculation method
STOT RE 2	H373	Calculation method
Asp. Tox. 1	H304	Calculation method
Aquatic Chronic 2	H411	Calculation method

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Attachment to the Safety Data Sheet

Trade name: Cleaner T-VR

Ford Internal Ref.: 200321 **Revision Date:** 08.04.2026

Involved Products:

	Finiscode	Part Number	Packaging
1	2 341 955	JU7J M5B401 AA	1 l